

Keysight Technologies

# Multi-frequency C-V Measurement of Semiconductors

Application Note

## Keysight E4980A and 4284A Precision LCR Meters

Parameters such as the capacitance of the oxide layer ( $C_{ox}$ ) and the density of substrate impurities ( $N_{sub}$ ) that are required in the evaluation of the manufacturing process of MOS type semiconductors can be derived by using measured C-V characteristics. To make an accurate evaluation of these processes, precise C-V measurements are required. Such measurements entail the following difficulties.

### Difficulties

1. There is no single instrument that can make C-V measurements from low to high frequencies.
2. It is difficult to compensate for the additional errors that occur when cable extensions or a prober are used.
3. The accuracy and reliability of the DC bias voltage are not sufficient to perform repeatable C-V measurements.

In the following discussion we will show how C-V measurements are performed with the E4980A and 4284A solving these problems.

## Solutions Offered by the E4980A and 4284A

### 1. Wide Frequency Range Measurements from 20 Hz to 2 MHz.

The program listing shown in the appendix was used to measure the C-V characteristics at 10 kHz, 100 kHz, and 1 MHz of the MOS device whose characteristics are shown in Figure 1.

Thus, the E4980A and the 4284A can single-handedly perform C-V measurements in both the low and high frequency ranges. This allows it to measure high-loss devices (semiconductors on large diameter wafers, etc.), which are difficult to measure at 1 MHz, at low frequencies (10 kHz, 100 kHz, etc.).




Figure 1. Multi-frequency C-V characteristics of a semiconductor

## 2. Compensation Functions for Cable Extensions and Probers.

In order to test semiconductor devices on a wafer, an extension cable and a prober are required. (See Figure 2 and 3.) The extension cable and the prober cause additional errors that greatly influence the test value. The E4980A and 4284A's 2m/4m Cable Length Operation function with 16048D/E test leads, Option 006 for 4284A, minimizes additional errors caused by using 2m/4m extension cables. The E4980A and 4284A's open/short/load compensation functions minimize errors caused by a prober. This powerful compensation function ensures highly accurate C-V measurements even when a prober is used.




Figure 2. Cable extension and prober connection in four-terminal pair (4TP) configuration




Figure 3. Cable extension and prober connection in two-terminal pair (2TP) configuration

### 3. Highly Accurate Internal Bias

Insufficient accuracy and stability of the bias voltage applied to a device prevents accurate C-V measurements. The E4980A and 4284A ensure the application of a stable bias voltage with a maximum accuracy of 0.1% (Option 001). This minimizes measurement errors due to bias voltage errors.

Table 1. E4980A Option 001 DC Bias Capability

Range	Resolution	Accuracy*
±0 to 5 V	330 µV	± 0.1% + 2 mV
±5.001 to 10 V	1 mV	± 0.1% + 2 mV
±10.002 to 20 V	2 mV	± 0.1% + 2 mV
±20.005 to 40 V	5 mV	± 0.1% + 2 mV

*\*This can only be used when the test signal level is < 2 Vrms*

Table 2. 4284A Option 001 DC Bias Capability

Range	Resolution	Accuracy*
±0.000 to 5 V	1 mV	± 0.1% + 1 mV
±4.002 to 8 V	2 mV	± 0.1% + 2 mV
±8.005 to 20 V	5 mV	± 0.1% + 5 mV
±20.01 to 40 V	10 mV	± 0.1% + 10 mV

*\*This can only be used when the test signal level is < 2 Vrms*

## Conclusion

The E4980A and 4284A feature a wide frequency range, powerful compensation functions, and highly accurate bias characteristics. This versatility of the meter guarantees highly accurate C-V measurements, and higher efficiency in the evaluation of semiconductor processes. Because the E4980A and 4284A can perform all of the low and high frequency C-V measurements singlehandedly, it will greatly contribute to the lowering of capital costs.

# Appendix 1. Keysight E4980A Sample Program List

```

10 ! ***** Keysight E4980A C-V MEASUREMENT SAMPLE PROGRAM *****
20 OPTION BASE 1
30 GCLEAR
40 PRINT CHR$(12) ! CLEAR DISPLAY
50 DIM C(3,101),Cn(3,101),Vbias(101)
60 INTEGER H1,H2,H3,Tm
70 DIM D(101,4)
80 ASSIGN @Ad TO 717;FORMAT ON ! DEFINE I/O PATH
90 ASSIGN @Pat TO 717;FORMAT OFF ! DEFINE I/O PATH
100 REMOTE @Ad ! SET E4980A TO REMOTE MODE
110 OUTPUT @Ad;" *Rst" ! RESET E4980A
120 OUTPUT @Ad;"VOLT:LEV 0.02V" ! SET OSC LEVEL TO 20mV
130 OUTPUT @Ad;"TRIG:SOUR BUS" ! GPIB TRIGGER MODE
140 OUTPUT @Ad;"FORM:DATA REAL" ! BINARY DATA TRANSFER
150 OUTPUT @Ad;"MEM:DIM DBUF,101" ! DEFINE BUFFER IN E4980A
160 OUTPUT @Ad;"MEM:FILL DBUF" ! ENABLE BUFFER TRANSFER
170 OUTPUT @Ad;"APER SHOR" ! SET INTEG TIME TO SHORT
180 GOSUB Corr
190 PRINT "CONNECT OUT AND PRESS CONTINUE"
200 PAUSE
210 PRINT CHR$(12) ! CLEAR DISPLAY
220 Holdtime=10 ! HOLD TIME = 10sec
230 Delaytime=.1 ! DELAY TIME = 100msec
240 Vbias(1)=-5 ! START BIAS VOLTAGE
250 Vstep=.1 ! 100mV BIAS STEP
260 OUTPUT @Ad;"TRIG:DEL "&VAL$(Delaytime) ! SET DELAY TIME
270 OUTPUT @Ad;"OUTP:DC:ISOL:STAT ON" ! DCI ISOLATION ON
280 OUTPUT @Ad;"BIAS:STATE ON" ! BIAS ON
290 Freq$(1)=" 1MHz"
300 Freq$(2)=" 100KHz"
310 Freq$(3)=" 10KHz"
320 FOR I=1 TO 3
330 OUTPUT @Ad;"FREQ"&Freq$(I) ! FREQUENCY SETTING
340 OUTPUT @Ad;"BIAS:VOLT "&VAL$(Vbias(1)) ! SET START BIAS VOLTAGE
350 PRINT TABXY(5,15);"HOLD TIME 10SEC"
360 WAIT Holdtime ! HOLD TIME
370 PRINT TABXY(5,15);"MEASURING at "&Freq$(I)
380 FOR J=1 TO 101
390 OUTPUT @Ad;"trig" ! TRIGGER E4980A
400 IF J=101 THEN 430
410 Vbias(J+1)=Vbias(J)+Vstep ! CHANGE BIAS VOLTAGE
420 OUTPUT @Ad;"BIAS:VOLT "&VAL$(Vbias(J+1)) ! SET BIAS VOLTAGE
430 NEXT J
440 OUTPUT @Ad;"MEM:READ? DBUF" ! READ BUFFER
450 ENTER @Pat;H1,H2,H3,D(*),Tm
460 FOR J=1 TO 101
470 C(I,J)=D(J,1)
480 NEXT J
490 IF MAX(C(*))=0 THEN Err CHECK IF MAX C VALUE IS 0
500 FOR J=1 TO 101
510 Cn(I,J)=C(I,J)/MAX(C(*)) ! NORMALIZE C VALUE
520 NEXT J
530 OUTPUT @Ad;"MEM:CLE DBUF;FILL DBUF" ! CLEAR DATA IN BUFFER
540 PRINT CHR$(12) ! CLEAR DISPLAY
550 NEXT I
560 OUTPUT @Ad;"BIAS:STATE OFF" ! BIAS OFF
570 GOSUB Plotting
580 GOTO Ending
590 !
600 ! ***** PLOT C-V *****
610 ! THE FOLLOWINGS ARE FOR PLOTTING THE MEASUREMENT DATA TO CRT.
620 !
630 Plotting: DEG ! SET ANGLE UNIT TO DEGREE
640 GRAPHICS ON
650 VIEWPORT 8,150,17,100 ! PLOT NUMBERS AND LABELS
660 WINDOW 0,100,0,100 !
670 LDIR 0 !
680 LORG 2 !
690 CSIZE 4 !
700 MOVE 45,15 !
710 LABEL "BIAS (V)" !
720 MOVE 8,23 !
730 LABEL "-5.0" !
740 MOVE 49,23 !
750 LABEL "0" !
760 MOVE 84,23 !
770 LABEL "5.0" !
780 MOVE 5,98 !

```

## Appendix 1. Keysight E4980A Sample Program List *continued...*

```

790 LABEL "1.0"                !
800 MOVE 65,5                  !
810 LABEL " 1MHz"              !
820 MOVE 65,10                 !
830 LABEL "100kHz"             !
840 MOVE 65,15                 !
850 LABEL " 10kHz"             !
860 MOVE 78,5                  !
870 DRAW 88,5                  !
880 LINE TYPE 8                !
890 MOVE 78,10                 !
900 DRAW 88,10                 !
910 LINE TYPE 3                !
920 MOVE 78,15                 !
930 DRAW 88,15                 !
940 LINE TYPE 1                !
950 LDIR 90                    !
960 MOVE 3,55                  !
970 LABEL "Cap/Cox"           !
980 LDIR 0                     !
990 MOVE 5,28                  !
1000 LABEL "0.0"               !
1010 MOVE 5,98                 !
1020 LABEL "1.0"               ! END PLOT NUMBERS AND LABELS
1030                            !
1040 VIEWPORT 25,125,40,95     ! DRAW AXES
1050 FRAME                     !
1060 WINDOW -5,-5,0,1         !
1070 AXES 1,-2,-5,0           ! END DRAW AXES
1080                            !
1090 FOR I=1 TO 3              ! PLOT DATA
1100   MOVE Vbias(1),Cn(1,1)    !
1110   FOR J=2 TO 101          !
1120     DRAW Vbias(J),Cn(I,J)  !
1130   NEXT J                  !
1140   LINE TYPE 3             !
1150   IF I=1 THEN LINE TYPE 8 !
1160 NEXT I                    ! END PLOT DATA
1170 LINE TYPE 1
1180 RETURN
1190 !
1200 Corr: ! ***** SUBROUTINE FOR CORRECTION *****
1210 ! THE FOLLOWINGS ARE FOR PERFORMING OPEN/SHORT COMPENSATION.
1220 !
1230 OUTPUT @Ad;"DISP:PAGE CSETUP" ! GO TO CORRECTION SETUP PAGE
1240 OUTPUT @Ad;"CORR:LENG 1:METH SING" ! CABLE LENGTH 1m, SINGLE COMPEN MODE
1250 OUTPUT @Ad;"CORR.SPOT1:FREQ 1MHz,STAT ON" ! SPOT FREQ 1 = 1MHz
1260 OUTPUT @Ad;"CORR.SPOT2:FREQ 100kHz,STAT ON" ! SPOT FREQ 2 = 100kHz
1270 OUTPUT @Ad;"CORR.SPOT3:FREQ 10kHz,STAT ON" ! SPOT FREQ 3 = 10kHz
1280 OUTPUT @Ad;"CORR:LOAD:STAT OFF" ! LOAD COMPEN OFF
1290 PRINT "OPEN COMPENSATION"
1300 PRINT TABXY(5,15);"PRESS CONTINUE"
1310 PAUSE
1320 PRINT TABXY(5,15);" "
1330 OUTPUT @Ad;"CORR.SPOT1:OPEN" ! PERFORM OPEN COMPEN AT SPOT FREQ 1
1340 OUTPUT @Ad;"CORR.SPOT2:OPEN" ! PERFORM OPEN COMPEN AT SPOT FREQ 2
1350 OUTPUT @Ad;"CORR.SPOT3:OPEN" ! PERFORM OPEN COMPEN AT SPOT FREQ 3
1360 OUTPUT @Ad;"*OPC?" ! CONFIRM OPEN MEASUREMENT COMPLETED
1370 ENTER @Ad;AS
1380 OUTPUT @Ad;"CORR:OPEN:STAT ON" ! OPEN COMPEN ON
1390 PRINT CHR$(12) ! CLEAR DISPLAY
1400 PRINT "SHORT COMPENSATION"
1410 PRINT TABXY(5,15);"PRESS CONTINUE"
1420 PAUSE
1430 PRINT TABXY(5,15);" "
1440 OUTPUT @Ad;"CORR.SPOT1:SHOR" ! PERFORM SHORT COMPEN AT SPOT FREQ 1
1450 OUTPUT @Ad;"CORR.SPOT2:SHOR" ! PERFORM SHORT COMPEN AT SPOT FREQ 2
1460 OUTPUT @Ad;"CORR.SPOT3:SHOR" ! PERFORM SHORT COMPEN AT SPOT FREQ 3
1470 OUTPUT @Ad;"*OPC?" ! CONFIRM SHORT MEASUREMENT COMPLETED
1480 ENTER @Ad;AS
1490 OUTPUT @Ad;"CORR.SHOR:STAT ON" ! SHORT COMPEN ON
1500 OUTPUT @Ad;"DISP:PAGE MEAS" ! GO TO MEASUREMENT PAGE
1510 PRINT CHR$(12) ! CLEAR DISPLAY
1520 RETURN
1530 !
1540 ! *****
1550 Err: PRINT "C-V MEASUREMENT FAILED."
1560 Ending: END

```

## Appendix 2. Keysight 4284A Sample program list

```

10 ! ***** Keysight 4284A C-V MEASUREMENT SAMPLE PROGRAM *****
20 OPTION BASE 1
30 GCLEAR
40 PRINT CHR$(12) ! CLEAR DISPLAY
50 DIM C(3,101),Cn(3,101),Vbias(101)
60 INTEGER H1,H2,H3,Tm
70 DIM D(101,4)
80 ASSIGN @Ad TO 717;FORMAT ON ! DEFINE I/O PATH
90 ASSIGN @Pat TO 717;FORMAT OFF ! DEFINE I/O PATH
100 REMOTE @Ad ! SET 4284A TO REMOTE MODE
110 OUTPUT @Ad;" *Rst" ! RESET 4284A
120 OUTPUT @Ad;"VOLT:LEV 0.02V" ! SET OSC LEVEL TO 20mV
130 OUTPUT @Ad;"OUTP:HPOW ON" ! BIAS OPTION ON
140 OUTPUT @Ad;"TRIG:SOUR BUS" ! GPIB TRIGGER MODE
150 OUTPUT @Ad;"FORM:DATA REAL" ! BINARY DATA TRANSFER
160 OUTPUT @Ad;"MEM:DIM DBUF,101" ! DEFINE BUFFER IN 4284A
170 OUTPUT @Ad;"MEM:FILL DBUF" ! ENABLE BUFFER TRANSFER
180 OUTPUT @Ad;"APER SHOR" ! SET INTEG TIME TO SHORT
190 GOSUB Corr
200 PRINT "CONNECT OUT AND PRESS CONTINUE"
210 PAUSE
220 PRINT CHR$(12) ! CLEAR DISPLAY
230 Holdtime=10 ! HOLD TIME = 10sec
240 Delaytime=.1 ! DELAY TIME = 100msec
250 Vbias(1)=-5 ! START BIAS VOLTAGE
260 Vstep=.1 ! 100mV BIAS STEP
270 OUTPUT @Ad;"TRIG:DEL "&VAL$(Delaytime) ! SET DELAY TIME
280 OUTPUT @Ad;"OUTP:DC-ISOL ON" ! DC BIAS ISOLATION ON
290 OUTPUT @Ad;"BIAS:STATE ON" ! BIAS ON
300 Freq$(1)=" 1MHz"
310 Freq$(2)=" 100KHz"
320 Freq$(3)=" 10KHz"
330 FOR I=1 TO 3
340 OUTPUT @Ad;"FREQ"&Freq$(I) ! FREQUENCY SETTING
350 OUTPUT @Ad;"BIAS:VOLT "&VAL$(Vbias(1)) ! SET START BIAS VOLTAGE
360 PRINT TABXY(5,15);"HOLD TIME 10SEC"
370 WAIT Holdtime ! HOLD TIME
380 PRINT TABXY(5,15);"MEASURING at "&Freq$(I)
390 FOR J=1 TO 101
400 OUTPUT @Ad;"trig" ! TRIGGER 4284A
410 IF J=101 THEN 440
420 Vbias(J+1)=Vbias(J)+Vstep ! CHANGE BIAS VOLTAGE
430 OUTPUT @Ad;"BIAS:VOLT "&VAL$(Vbias(J+1)) ! SET BIAS VOLTAGE
440 NEXT J
450 OUTPUT @Ad;"MEM:READ? DBUF" ! READ BUFFER
460 ENTER @Pat;H1,H2,H3,D(*),Tm
470 FOR J=1 TO 101
480 C(I,J)=D(J,I)
490 NEXT J
500 IF MAX(C(*))=0 THEN Err ! CHECK IF MAX C VALUE IS 0
510 FOR J=1 TO 101
520 Cn(I,J)=C(I,J)/MAX(C(*)) ! NORMALIZE C VALUE
530 !PRINT Cn(I,J) ! PRINT NORMALIZED C VALUE
540 NEXT J
550 OUTPUT @Ad;"MEM:CLE DBUF;FILL DBUF" ! CLEAR DATA IN BUFFER
560 PRINT CHR$(12) ! CLEAR DISPLAY
570 NEXT I
580 OUTPUT @Ad;"BIAS:STATE OFF" ! BIAS OFF
590 GOSUB Plotting
600 GOTO Ending
610 !
620 ! ***** PLOT C-V *****
630 ! THE FOLLOWINGS ARE FOR PLOTTING THE MEASUREMENT DATA TO CRT.
640 !
650 Plotting: DEG ! SET ANGLE UNIT TO DEGREE
660 GRAPHICS ON
670 VIEWPORT 8,150,17,100 ! PLOT NUMBERS AND LABELS
680 WINDOW 0,100,0,100 !
690 LDIR 0 !
700 LORG 2 !
710 CSIZE 4 !
720 MOVE 45,15 !
730 LABEL "BIAS (V)" !
740 MOVE 8,23 !
750 LABEL "-5.0" !
760 MOVE 49,23 !
770 LABEL "0" !
780 MOVE 84,23 !
790 LABEL "5.0" !

```

## Appendix 2. Keysight 4284A Sample program list *continued...*

```

800 MOVE 5,98 !
810 LABEL "1.0" !
820 MOVE 65,5 !
830 LABEL " 1MHz" !
840 MOVE 65,10 !
850 LABEL "100kHz" !
860 MOVE 65,15 !
870 LABEL " 10kHz" !
880 MOVE 78,5 !
890 DRAW 88,5 !
900 LINE TYPE 8 !
910 MOVE 78,10 !
920 DRAW 88,10 !
930 LINE TYPE 3 !
940 MOVE 78,15 !
950 DRAW 88,15 !
960 LINE TYPE 1 !
970 LDIR 90 !
980 MOVE 3,55 !
990 LABEL "Cap/Cox" !
1000 LDIR 0 !
1010 MOVE 5,28 !
1020 LABEL "0.0" !
1030 MOVE 5,98 !
1040 LABEL "1.0" ! END PLOT NUMBERS AND LABELS
1050 !
1060 VIEWPORT 25,125,40,95 ! DRAW AXES
1070 FRAME !
1080 WINDOW -5,5,0,1 !
1090 AXES 1,-2,-5,0 ! END DRAW AXES
1100 !
1110 FOR I=1 TO 3 ! PLOT DATA
1120 MOVE Vbias(1),Cn(I,1) !
1130 FOR J=2 TO 101 !
1140 DRAW Vbias(J),Cn(I,J) !
1150 NEXT J !
1160 LINE TYPE 3 !
1170 IF I=1 THEN LINE TYPE 8 !
1180 NEXT I ! END PLOT DATA
1190 LINE TYPE 1
1200 RETURN
1210 !
1220 Corr: ! ***** SUBROUTINE FOR CORRECTION *****
1230 ! THE FOLLOWINGS ARE FOR PERFORMING OPEN/SHORT COMPENSATION.
1240 !
1250 OUTPUT @Ad;"DISP:PAGE CSETUP" ! GO TO CORRECTION SETUP PAGE
1260 OUTPUT @Ad;"CORR:LENG 1;METH SING" ! CABLE LENGTH 1m, SINGLE COMPEN MODE
1270 OUTPUT @Ad;"CORR:SPOT1:FREQ 1MHz;STAT ON" ! SPOT FREQ 1 = 1MHz
1280 OUTPUT @Ad;"CORR:SPOT2:FREQ 100kHz;STAT ON" ! SPOT FREQ 2 = 100kHz
1290 OUTPUT @Ad;"CORR:SPOT3:FREQ 10kHz;STAT ON" ! SPOT FREQ 3 = 10kHz
1300 OUTPUT @Ad;"CORR:LOAD:STAT OFF" ! LOAD COMPEN OFF
1310 PRINT "OPEN COMPENSATION"
1320 PRINT TABXY(5,15);"PRESS CONTINUE"
1330 PAUSE
1340 PRINT TABXY(5,15);" "
1350 OUTPUT @Ad;"CORR:SPOT1:OPEN" ! PERFORM OPEN COMPEN AT SPOT FREQ 1
1360 OUTPUT @Ad;"CORR:SPOT2:OPEN" ! PERFORM OPEN COMPEN AT SPOT FREQ 2
1370 OUTPUT @Ad;"CORR:SPOT3:OPEN" ! PERFORM OPEN COMPEN AT SPOT FREQ 3
1380 OUTPUT @Ad;"*OPC?" ! CONFIRM OPEN MEASUREMENT COMPLETED
1390 ENTER @Ad:AS
1400 OUTPUT @Ad;"CORR:OPEN:STAT ON" ! OPEN COMPEN ON
1410 PRINT CHR$(12) ! CLEAR DISPLAY
1420 PRINT "SHORT COMPENSATION"
1430 PRINT TABXY(5,15);"PRESS CONTINUE"
1440 PAUSE
1450 PRINT TABXY(5,15);" "
1460 OUTPUT @Ad;"CORR:SPOT1:SHOR" ! PERFORM SHORT COMPEN AT SPOT FREQ 1
1470 OUTPUT @Ad;"CORR:SPOT2:SHOR" ! PERFORM SHORT COMPEN AT SPOT FREQ 2
1480 OUTPUT @Ad;"CORR:SPOT3:SHOR" ! PERFORM SHORT COMPEN AT SPOT FREQ 3
1490 OUTPUT @Ad;"*OPC?" ! CONFIRM SHORT MEASUREMENT COMPLETED
1500 ENTER @Ad:AS
1510 OUTPUT @Ad;"CORR:SHOR:STAT ON" ! SHORT COMPEN ON
1520 OUTPUT @Ad;"DISP:PAGE MEAS" ! GO TO MEASUREMENT PAGE
1530 PRINT CHR$(12) ! CLEAR DISPLAY
1540 RETURN
1550 !
1560 ! *****
1570 Err: PRINT "C-V MEASUREMENT FAILED."
1580 Ending: END

```

**myKeysight**

**myKeysight**

[www.keysight.com/find/mykeysight](http://www.keysight.com/find/mykeysight)

A personalized view into the information most relevant to you.



**Three-Year Warranty**

[www.keysight.com/find/ThreeYearWarranty](http://www.keysight.com/find/ThreeYearWarranty)

Keysight's commitment to superior product quality and lower total cost of ownership. The only test and measurement company with three-year warranty standard on all instruments, worldwide.



**Keysight Assurance Plans**

[www.keysight.com/find/AssurancePlans](http://www.keysight.com/find/AssurancePlans)

Up to five years of protection and no budgetary surprises to ensure your instruments are operating to specification so you can rely on accurate measurements.



[www.keysight.com/quality](http://www.keysight.com/quality)

Keysight Technologies, Inc.  
DEKRA Certified ISO 9001:2008  
Quality Management System

**Keysight Channel Partners**

[www.keysight.com/find/channelpartners](http://www.keysight.com/find/channelpartners)

Get the best of both worlds: Keysight's measurement expertise and product breadth, combined with channel partner convenience.

This document was formerly known as product note number 369-5.

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at: [www.keysight.com/find/contactus](http://www.keysight.com/find/contactus)

**Americas**

Canada	(877) 894 4414
Brazil	55 11 3351 7010
Mexico	001 800 254 2440
United States	(800) 829 4444

**Asia Pacific**

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 112 929
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Other AP Countries	(65) 6375 8100

**Europe & Middle East**

Austria	0800 001122
Belgium	0800 58580
Finland	0800 523252
France	0805 980333
Germany	0800 6270999
Ireland	1800 832700
Israel	1 809 343051
Italy	800 599100
Luxembourg	+32 800 58580
Netherlands	0800 0233200
Russia	8800 5009286
Spain	0800 000154
Sweden	0200 882255
Switzerland	0800 805353
	Opt. 1 (DE)
	Opt. 2 (FR)
	Opt. 3 (IT)
United Kingdom	0800 0260637

For other unlisted countries:  
[www.keysight.com/find/contactus](http://www.keysight.com/find/contactus)  
(BP-07-10-14)